

Data Link Simulator II



- Simulates communications facilities
- 78 data rates from 1,200 to 50M bps
- Inserts delays up to 1.999 second in each direction
- Inserts errors and timing slips in each direction
- Supports T-1, E-1, RS232, V.35, RS422/RS530, X.21, HSSI, T-3 and E-3
- Context-sensitive help screens

The TELINC Data Link Simulator II simulates a communications link, inserting delays and introducing errors so users can determine what effects these impairments will have on their systems. The Simulator II includes a 35 x 20 character color LCD display. Context-sensitive help screens make it easy to use, without training or reference to a manual.

The TELINC Simulator II can be used in many applications including testing protocols and error correction techniques, checking new equipment prior to field installation and measuring performance and reliability in various operating environments. It can simulate a variety of communications facilities including:

- A leased line with modems on each end
- A DDS line with CSU/DSUs on each end
- A T-1 line with T-1 CSUs on each end
- A satellite facility with modems on each end
- A T-3 facility with T-3 CSUs on each end
- A 2.048 Mbps facility with DTUs (Digital Terminating Units) on each end

The Simulator II includes six pairs of interfaces as standard equipment: RS232, RS422/RS530, V.35, X.21 and T-1 and E-1. It can introduce propagation delays in either or both directions and can inject logic, ones, zeros, timing slips, bit, burst, frame,

BPV, CRC, FDL, signaling, block, C-Bit and P-Bit errors in either or both directions. Propagation delays can be up to 1.999 seconds per direction for speeds up to 2.048 Mbps and up to 500 milliseconds for speeds from 8.192M to 50 Mbps. Delays, errors and speeds can be different in each direction.

The Data Link Simulator II is easy to use. All operating parameters, including interfaces, speeds, delays, errors and control signals are illustrated on a single screen. Parameters are selected by scrolling through values stored in the Simulator II.

All operations can be performed with only a few keys. At any point, the user can get help by hitting the HELP key.

Data Link Simulator II

Specifications



Rear Panel of DLS II showing all standard interfaces and two available option slots.

Base Unit

Speeds	78 standard speeds from 1,200 bps to 8.192 Mbps	
Interfaces, two each	RS232 RS530/RS422 V.35 X.21 T-1 and E-1 (G.703)	DB25P 25-pin female connector DB25P 25-pin female connector 34-pin Winchester female connector DB15P 15 pin female connector RJ48C 8 position modular in parallel with bantam and dual BNCs.
Optional Module Speeds	Up to 50 Mbps	
Interfaces, two each	T-3 E-3 HSSI	75 ohm BNC connectors 75 ohm BNC connectors 50 pin HSSI connectors
Propagation Delays	Up to 1.999 second per direction for speeds up to 2.048 Mbps Up to 0.5 seconds (500 ms) per direction for speeds to 50 Mbps Delay is selectable in 1 millisecond increments	
RTS/CTS Delays	Up to 999 millisecs in 1 millisecond increments	
Errors	Logic (bit) errors, Ones, Zeros, Burst errors, Block errors, Framing errors, BPVs, CRCs, C-Bit errors, P-Bit errors, Error seconds and Slips	
Error Frequency	1x10 ⁶ to 1x10 ¹² bits, Random Secs, Manual Gap up to 99999999 bits, Gap up to 99999999 milliseconds 9999 Blocks	
Timing	Internal, external and locked External clock – TTL level	
Control Signals	Request To Send (RTS), Clear To Send (CTS) Data Set Ready (DSR), Carrier Detect (CD) Data Terminal Ready (DTR)	
Power	90 - 230V AC 50 to 60 Hz 7.2 watts 25 BTU/hr	
Dimensions	3.5" (8.9 cm) h x 10" (25.4 cm) w x 12" (30.5 cm) d	
Weight	12 lbs (5.5 kg)	
Environmental		
Operating Temperature	0 to 50° C, 32 to 122° F	
Relative Humidity	0 to 95% non-condensing	
Part Numbers for Ordering	TL205201 - Base Unit with dual T-1, E-1, RS232, RS422/RS530 V.35 and X.21 interfaces. TL205208 - Optional dual T-3, E-3 and HSSI module. TL205209 - Rackmount kit – includes 2 brackets	

TELINC

5941 Atkinson Road, Suite B
New Hope, PA 18938
800-257-5110 215-598-0300
FAX 215-598-8034 www.telinc.com

Printed in USA.
Specifications subject to
change without notice.
© Telinc Corp 2006-2014